



RECOMMENED P.C.B LAYOUT(TOP VIEW)  
GENERAL TOLERANCE ±0.05

NOTE:  
1. ELECTRICAL CHARACTERISTICS  
1-1. CONTACT RESISTANCE:  
80 milliohms MAX.  
1-2. INSULATION RESISTANCE:  
1,000 Megohms MIN.  
1-3. DIELECTRIC WITHSTANDING  
VOLTAGE: 500V AC  
FOR 1 MINUTE.  
2. MECHANICAL CHARACTERISTICS  
RETENTION FORCE:MIN.100gf/PIN  
3. RoHS 2002/95/EC COMPLIANT.

ITEM	PAPT NAMF	QTY	MATERIAL	FINISHING
③	PEG	1	COPPER ALLOY	
②	Terminal	8	COPPER ALLOY	
①	Housing	1	HI-TEMP.PLASIC UL 94V-0	BLACK

MARK	DESCRIPTION	DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES	DSND	DATE	SCALE: N/A	MODEL TYPE: TF CARD CONN
Δx					ANGLAR ±5°	DWN	DATE	VIEW:	PART NO.:
Δx					L ≤ 4 ±0.2	CHKD	DATE	UNIT: mm	DWG NO.:
Δx					4 < L ≤ 16 ±0.3	APPD	DATE	SIZE: A4	XKTF-004
					16 < L ≤ 63 ±0.4	KXB INDUSTRIAL PRECISION CO.,LIMITED			WEIGHT
					L > 63 ±0.5				1.0g
									SHEET
									1/1
									REVISION
									A0